



ICEMAKER filter

The ICEMAKER 6" Series Granulated Activated Carbon, GAC, reduce chlorine, other unpleasant tastes and odors and provide a nominal 5µ protection against particulate matter.

The ICEMAKER GAC also reduces hard water scale build up. Complete installation and operation instructions are available with the product.

FEATURES & BENEFITS:

- connections available: built in 1/4" JACO-style compression fittings
- Suitable for installation with ice-makers, coffee and tea makers and water fountains to provide clean, fresh tasting water.
- The all polypropylene construction with pre and post filters provide a corrosion resistant body with a life of up to one year under normal conditions.
- Standard dimensions: nominal diameter 5,20cm (2") by 17,50cm long (6")

SPECIFICATIONS:

- Rated Service Flow: 1,60 liters/min (0.42 gpm)
- Capacity: 2.300 liters (605 gal)
- Operating Temperature Range: 4° to 38° C (40° -100° F)
- Operating Pressure Range: 1.4 to 6.9 bar (20 -100 psi)

Carbon filters are not for use where water is microbiologically unsafe or of unknow quality without adequate disinfection before or after the unit.

CHLORINE REDUCTION PERFORMANCE:

Mean influent concentration (ppm)	Mean effluent concentration (ppm)	Max effluent concentration (ppm)	Percent reduction
1,9	0.09	0.25	95.2

Notes: test performed at 1.60 liters/min, 4,2 bar, pH 7.5, 20°C



Product Code	Description		Packing units	Volume cu.mt.
1013900C	ICEMAKER 1/4" 6"	1/4" GAC for IceMakers	10	0.008
1013906C	IN-LINE 1/4" 6"	1/4" Empty vessel for IceMakers	10	0.008