


FILTER HOUSINGS MOD. 202



CONTENITORE IN 2 PEZZI, TESTA STAFFABILE / 2 PIECE HOUSING, BRACKET MOUNTABLE HEAD



mod. 202 - mod 202

WF Code	Description	Size inches	In/Out inches	Brass thread	Bowl material	Pack units
1202786C	CONT. 202-1/4-5-SAN	5	1/4	No	SAN	12
1202787C	CONT. 202-3/8-5-SAN	5	3/8	No	SAN	12
1202905C	CONT. 202-1/2-5-SAN	5	1/2	No	SAN	12
1202906C	CONT. 202-3/4-5-SAN	5	3/4	No	SAN	12
1202785C	CONT. 202-1/4-5-PP	5	1/4	No	PP	12
1202796C	CONT. 202-3/8-5-PP	5	3/8	No	PP	12
1202907C	CONT. 202-1/2-5-PP	5	1/2	No	PP	12
1202908C	CONT. 202-3/4-5-PP	5	1/2	No	PP	12
1202929C	CONT. 202-1/4-9-SAN	9 3/4	1/4	No	SAN	12
1202925C	CONT. 202-3/8-9-SAN	9 3/4	3/8	No	SAN	12
1202900C	CONT. 202-1/2-9-SAN	9 3/4	1/2	No	SAN	12
1202901C	CONT. 202-3/4-9-SAN	9 3/4	3/4	No	SAN	12
1202910C	CONT. 202-1/4-9-PP	9 3/4	1/4	No	PP	12
1202902C	CONT. 202-3/8-9-PP	9 3/4	3/8	No	PP	12
1202903C	CONT. 202-1/2-9-PP	9 3/4	1/2	No	PP	12
1202904C	CONT. 202-3/4-9-PP	9 3/4	3/4	No	PP	12
1202768C	CONT. 202-1/4-20-PP	20	1/4	No	PP	4
1202923C	CONT. 202-3/8-20-PP	20	3/8	No	PP	4
1202769C	CONT. 202-1/2-20-PP	20	1/2	No	PP	4
1202795C	CONT. 202-3/4-20-PP	20	3/4	No	PP	4

ACCESSORI / ACCESSOIRES

1202034C	CHIAVE PLASTICA 202 BLU	Spanner for Housings Mod. 202 - 122 -132 - Counter-Tops
----------	-------------------------	---

DATI TECNICI / TECHNICAL DATA

Testa / Head	Polipropilene talco / Talc polypropylene
Vaso / Bowl	SAN trasparente / SAN clear PP opaco bianco / PP white opaque
O-ring / O-ring	NBR
Pressione max. d'esercizio / Max. working pressure	8,6 bar (125 psi)
Temperatura max. in esercizio continuo / Max. temperature continuous service	40° c

