



**W.F. SRL**

**K-osmo 100METAL** is an osmosi system unlike any other on the market , thanks to latest generation technologies that allow a reduced use of conventional hydraulic fittings .  
Each of its parts has been designed to make **K-osmo 100 METAL** the safest system on the market and the easiest to manage both for diagnostics and for periodic maintenance.



K-osmo 100 METAL

- Power supply 220V AC 50 Hz, 115W
- Filter management by electronic control unit that manage:  
Anti-flooding system  
Washing of membranes  
Security lock after 15 minutes of operation continuous  
Anti-stagnation system
- 100 l/h , Water treated, nominal value @ 25 ° C  
2.1l / min waste
- 2 x 180 GPD Membranes:  
Recovery ratio: 42%  
Rejection: 95%
- Booster pump 4.2 LpH
- FC 130 Carbon-Block bayonet filter
- ST 130 bayonet bracket
- Installation kit with Faucet
- Weight: 8,0 kg
- Overall dimensions (mm): 378 x435 H96.
- CE certified products in compliance with the D.M. 174 of 06/04/2004 and to the D.M.25 of 07/02/2012

K-OSMO 100 METAL						
VERSIONE VERSION	DESCRIZIONE DESCRIPTION	ACQUA TRATTATA WATER TREAT. CAPACITY	MEMBRANE	DISPLAY	PRE FILTRAZIONE PRE FILTRATION	PESO WEIGHT Kg.
K-OSMO 100 METAL	2 MEMBRANES	100 L/H	180 GPD	NO	INTERNA INTERNAL	6,5