

The **ICEMAKER 6"** Series Granulated Activated Carbon, GAC, reduce chlorine, other unpleasant tastes and odors and provide a nominal 5µ protection against particulate matter.

The **ICEMAKER GAC** also reduces hard water scale build up. Complete installation and operation instructions are available with the product.



mod. **ICEMAKER**

**CHLORINE REDUCTION PERFORMANCE:**

Mean influent concentration (ppm)	Mean effluent concentration (ppm)	Max effluent concentration (ppm)	Percent reduction
1,9	0.09	0.25	95.2

Notes: test performed at 1.60 liters/min, 4,2 bar, pH 7.5, 20°C

WF Code	Description	Volume cu.mt.	Pack units
1013900C	ICEMAKER 1/4" 6"	1/4" GAC for IceMakers	10
1013906C	IN-LINE 1/4" 6"	1/4" Empty vessel for IceMakers	10

**FEATURES & BENEFITS**

Connections available: built in 1/4" JACO-style compression fittings


Suitable for installation with ice-makers, coffee and tea makers and water fountains to provide clean, fresh tasting water.

The all polypropylene construction with pre and post filters provide a corrosion resistant body with a life of up to one year under normal conditions.

Standard dimensions: nominal diameter 5,20cm (2" ) by 17,50cm long (6" )

**SPECIFICATIONS:**

Rated Service Flow:	1,60 liters/min (0.42 gpm)
Capacity:	2.300 liters (605 gal)
Operating Temperature Range:	4° to 38° C (40° -100° F)
Operating Pressure Range:	1.4 to 6.9 bar (20 -100 psi)
Carbon filters are not for use where water is microbiologically unsafe or of unknow quality without adequate disinfection before or after the unit.	



The In-line 10" Series Granulated MEDIA is perfect to be customised because of your need, filled by treatment media and provide a nominal 5µ protection against particulate matter. Complete installation and operation instructions are available with the product.



## IN-LINE VESSELS FOR GRANULATED MEDIA

WF Code	Description		Volume cu.mt.	Pack units
1013909NM	IN-LINE 1/4" quot; 10 DEMINERAL	1/4" In-line MB478	0.008	10
1013909C	IN-LINE 1/4" quot; 10 GAC	1/4" In-line GAC	0.008	10
1013911C	IN-LINE 1/8" quot; 10 GAC	1/8" In-line GAC	0.008	10

### FEATURES & BENEFITS:

connections available: 1/8", 1/4", 3/8"

The all polypropylene construction with pre and post filters provide a corrosion resistant body with a life of up to one year under normal conditions.

Standard dimensions: nominal diameter 5.08cm (2") by 25.4cm long (10")

### SPECIFICATIONS:

Rated Service Flow: 2.84 liters/min (0.75 gpm)

Capacity: depend on the MEDIA

Operating Temperature Range: 4° -38° C (40° - 100° F)

Operating Pressure Range: 1.4 - 6.9 bar (20 -100 psi)