

CARBON FILTER CARTRIDGES MOD. CA

CARTUCCIA IN CARBONE GRANULARE ATTIVATO / GRANULAR ACTIVATED CARBON CARTRIDGE



mod. CA - mod CA

WF Code	Description	Size inches	Filter material	Canister body	Pack units
EA5	CART.CARBONI 5" SAN CLEAR	5	GAC	Clear	32
EA7	CART.CARBONI 7" SAN CLEAR	7	GAC	Clear	16
EA20	CART.CARBONI 20" SAN CLEAR	20	GAC	Clear	20
1009902CS	CART. MOD C (9-CA-T)	9 3/4	GAC	Clear	16
1009928CS	CART. MOD C (20-CA-T)	20	GAC	Clear	20
1009927CS	CART. MOD C (9-CA-O-POREX)	9 3/4	GAC	Opaque	16
1009929CS	CART. MOD C (20-CA-O-POREX)	20	GAC	Opaque	20
1009941CS	CART. MOD C (9-CA-T-POREX)	9 3/4	GAC	Clear	16
1009942CS	CART. MOD C (20-CA-T-POREX)	20	GAC	Clear	20
1004020	CART. JUMBO 10 GAC	9 3/4	GAC	White	-
1004021	CART. JUMBO 20 GAC	20	GAC	White	-

APPLICAZIONI

rimozione di odori e sapori sgradevoli dell'acqua, riduzione del cloro residuo utilizzato per la sterilizzazione dell'acqua, riduzione di contaminanti organici, sistemi di trattamento domestici, nell'industria alimentare e cosmetica, acque di processo, pre e post trattamento nei sistemi ad osmosi inversa.

APPLICATIONS

Bad taste and odour removal, reduction of chlorine and organic contaminants from water, domestic water treatment systems, food and cosmetics industries, process waters, pre and post treatment in reverse osmosis units.

DATI TECNICI / TECHNICAL DATA

Temperatura max d'esercizio / Max operating temperature

40° c

OPAQUE